The Technical Parameters of Flexible Conveyor		
1	Model	GY-FC1
2	Power	AC 220V/sph,AC 380V/3ph
3	Output(KW)	0.37 double driven motor
4	Frame	Carbon Steel, SUS, Aluminum
5	Chain Width(mm)	44, 63, 83, 103
6	Min. diameters(mm)	700, 750, 750, 800
7	Convey Height(mm)	≤3000(can be customized)
8	Speed (meter/min)	≤45 (can be customized)
9	Capacity(kg/m)	≤10 (can be customized)
Note: all the datas are for your refernce only,for the futher information please provide your requirement to us.		





The Technical Parameters of Flexible Conveyor		
1	Model	GY-FC2
2	Power	AC 220V/sph,AC 380V/3ph
3	Output(KW)	Can be customized
4	Frame	SUS, Aluminum
5	Chain Type	plain chain,friction top chain,cleated chain
6	Chain Width(mm)	44,63,83,103,140,150
7	Conveyor Width (mm)	45,65,85,105,145,155
8	Conveyor Length(mm)	≤3000(can be customized)
9	Conveyor Height(mm)	≥300(can be customized)
10	Speed (meter/min)	≤60(can be customized)
11	Capacity(kg/m)	10(horizontal transfer), 4(vertical tranfer)
12	Accessories	side plate,roller plate,nylon plate,bottom cover
Note: all the datas are for your refernce only,for the futher information please provide your requirement to us.		



